
In a stream of Slow-Steam,

New Maintenance Method for a pressure jet type burner of Aux. boiler.



MGO-fitting

Many of VOLCANO HFO Burners can be fitted to MGO (Marine Gas Oil) -use. Please contact to VOLCANO.

*The vessels in ECA(Emission Control Area) have to use low sulfer oil(0.10wt%) from 1st JAN, 2015.

Gas-fitting

Some of VOLCANO Oil Burners can be remodeled to Gas-use.

Please contact to VOLCANO.

Maintenance-cycle

In order to provide the required and satisfactory performance, the periodic check and maintenance are essential. For example, shortest interval for checking and cleaning of a burner is about 1 week. A sprayer-unit including an atomizer and a swirler should be checked and cleaned once per a week.

[Example of 1 year-maintenace-parts]

ATOMIZER, PILOT ATOMIZER, IGNITION ELECTRODE, SWIRLER, FLAME EYE ELEMENT (SENSOR), etc [Example of 3 years-maintenance-parts]

CAP NUT, SPRAYER, IGNITION CABLE, OIL SEAL FOR F.O. PUMP, PRESSURE GAUGE, COMPOUND GAUGE, etc

After-Sales Service

VOLCANO's After-sales Seavice Stands on Customers' Satisfaction.

VOLCANO considers after-sales service, including maintenance, to be an integral part of product quality control. The Company makes the constant effort to ensure customer satisfaction.

Systems are already in place to supply spare and replacement parts as quickly as possible to all main points world wide, and also to provide expert consulting services.

It is due to this kind of service and support that customers can fully rely on VOLCANO products.

Contact VOLCANO (on Products, Parts and After-sales service)

Combustion Engineering Division VOLCANO Co., Ltd.

info-m@volcano.co.jp FAX +81 6 6396 7609 TEL +81 6 6392 5541 http://www.volcano.co.jp/

1-3-38, Nonaka-kita, Yodogawa-ku, Osaka 532-0034 Japan